

Overview



SITRANS FUH1010 clamp-on non-intrusive ultrasonic flowmeter is ideal for applications carrying crude oil, refined petroleum or liquefied gas.

SITRANS FUH1010 has three application areas: Interface detectors, precision volume or standard volume flowmeters.

Benefits

For all FUH1010 products

- Easy installation; no need to cut pipe or stop flow
- Minimal maintenance; external sensors do not require periodic cleaning
- No moving parts to foul or wear
- No pressure drop or energy loss
- Wide turn-down ratio, 30:1
- Choice of single, dual, or optional, three or four path versions.
 - Single path version reduces initial investment
 - Two or optional three and four path versions provide higher accuracy, especially where limited straight run or poor flow profile exists
- WideBeam technology
 - Helps provide improved accuracy over a wide range of liquid conditions and flow rates
 - Accommodates pipelines transporting multiple liquid products
- ZeroMatic Path automatically corrects for zero drift without stopping flow

Interface detectors

- Outputs liquid density and API as a direct replacement for intrusive densitometers
- Exceptional repeatability is maintained, independent of changes in temperature, pressure or viscosity
- No need for straight run

Precision volume

- Moderate cost
- Precise measurement is maintained with automatic „Reynolds Number“ compensation for temperature and viscosity changes.

Standard volume

- Exceptional repeatability is maintained, independent of changes in temperature, density or viscosity
- Batch interface and product quality diagnostics provided
- Density and API outputs provided
- Scraper („pig“) detection provided

Application

Interface detectors

- Precise identification of interfaces on multi-liquid pipelines
- Rapid and precise scraper “pig” indication
- Product identification
- Density indication

Precision volume

- Applications with multiple liquids having a wide viscosity range
- Automatic gross volume compensation due to viscosity changes

Standard volume

- Standard (net) volume flow measurement
- Suitable for use in leak detection systems
- Mass flow output measurement
- Interface detection
- „Pig“ detection
- Chemical and petrochemical processing

Design

FUH1010 is available in three enclosures:

- IP65 (NEMA 4X) Enclosure constructed of fiberglass reinforced polyester with stainless steel hardware and polyester keypad
 - Single path
 - Dual path
 - Optional four path
- IP65 (NEMA 7) Compact explosionproof enclosure constructed of cast aluminum with glass window, stainless steel hardware
 - Single path
 - Dual path (option)
- IP66 (NEMA 7) Wall mount explosionproof enclosure constructed of cast aluminum, stainless steel hardware, with glass window
 - Single path
 - Dual path
 - Four path (optional)
- There are 2 types of mounting assemblies
 - Aluminum mounting frames (default)
 - Stainless steel weld seal (optional)

Function

- IP65 (NEMA 4X) and IP66 (NEMA 7) flow meters have integral 33 button keypads and large (128 x 240 pixel) graphic displays visible up to 12 m (40 ft) away
- IP65 (NEMA 7) compact flow meters has a 2 x 16 alphanumeric LCD display
- Current, voltage, status alarm, frequency and RS232 outputs (see specification section for details)
- Analog inputs (see specification section for details)
- ZeroMatic Path automatically corrects for zero drift
- Bidirectional flow operation
- 1 MByte data logger with both site and data logger storage
- English, spanish, german, italian and french language options

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUH1010 (Oil)

Technical specifications

Specifications for interface detectors

Accuracy

Accuracy	± 0.05 of API No.
Repeatability	± 0.01 of API No.

Specifications for volumetric and mass flowmeters

Input

Flow range	± 12 m/s (± 40 ft/s), bidirectional
Flow sensitivity	0.0003 m/s (0.001 ft/s), flow rate independent

Accuracy

Typical accuracy	± 0.5 to 1% of flow
Calibratable accuracy	± 0.15% ... 0.3% of flow, depending on version
Batch repeatability	± 0.05% of flow, maximum

Specifications for all FUH1010 products

Input

Pipe size	6.4 mm ... 9.14 m (0.25" ... 360")
Analog inputs	<ul style="list-style-type: none"> Current: 4 x 4 ... 20 mA (IP65 (NEMA 7) enclosure has (2))

Output

Standard outputs	<ul style="list-style-type: none"> Current: 4 x 4 ... 20 mA (1 kΩ at 30 VDC) Voltage: 2 x 0 ... 10 V DC (5 kΩ minimum) (None for IP65 (NEMA 7) enclosure) 1 x 0 ... 5 kHz Pulse Rate, Digital Quad. (None for IP65 (NEMA 7) enclosure) RS232 Serial Port
Extended outputs	<ul style="list-style-type: none"> MODBUS (not for IP65 (NEMA 7) enclosure) Up to 4 x additional 4 ... 20 mA (not for IP65 (NEMA 7) enclosure) 4 x Mercury wetted relays (not for IP65 (NEMA 7) enclosure) Up to 4 x digital pulse (not for IP65 (NEMA 7) enclosure)
Status/Alarm I/O	<ul style="list-style-type: none"> 4 x Programmable relays (not for IP65 (NEMA 7) enclosure) 2 x Optically coupled output logic gates (for IP65 (NEMA 7) enclosure, only) 1 x Totalizer clear switch input (not for IP65 (NEMA 4X) enclosure)¹⁾ 1 x Totalizer hold switch input (not for IP65 (NEMA 7) enclosure)¹⁾ 1 x Opto iso. totalizer clear switch input (for IP65 (NEMA 7) enclosure, only)¹⁾ 1 x Opto iso. totalizer hold switch input (for IP65 (NEMA 7) enclosure, only)¹⁾

Accuracy

Zero Drift	0.0003 m/s (0.001 ft/s), with ZeroMatic Path active (not provided for interface detector)
Data refresh rate	5 Hz

Rated operation conditions

Degree of protection	<ul style="list-style-type: none"> Wall mount enclosure Compact explosionproof Wall mount explosionproof 	<ul style="list-style-type: none"> IP65 (NEMA 4X) IP65 (NEMA 7) IP66 (NEMA 7)
Liquid temperature	<ul style="list-style-type: none"> Standard Optional 	<ul style="list-style-type: none"> -40 ... +120 °C (-40 ... +250 °F) -40 ... +230 °C (-40 ... +450 °F)
Ambient temperature		-18 ... +60 °C (0 ... 140 °F)

Design

Dimensions	see SITRANS F US Clamp-on „System info and selection guide“
Weight	see diagrams

Power supply

<ul style="list-style-type: none"> IP65 (NEMA 4X) and IP66 (NEMA 7) Wall Mount IP65 (NEMA 7) Compact 	<ul style="list-style-type: none"> 90 ... 240 V AC, 50 ... 60 Hz, 30 VA or 9 ... 36 V DC, 12 W 90 ... 240 V AC, 50 ... 60 Hz, 15 VA or 9 ... 36 V DC, 10 W
--	--

Indication and operation

Data logger memory	1 MByte	
Display	<ul style="list-style-type: none"> IP65 (NEMA 4X) and IP66 (NEMA 7) Enclosures IP65 (NEMA 7) Enclosure 	<ul style="list-style-type: none"> 128 x 240 pixel LCD with backlight 2 x 16 Alphanumeric LCD Display
Keypad	<ul style="list-style-type: none"> IP65 (NEMA 4X) and IP66 (NEMA 7) Enclosures IP65 (NEMA 7) Enclosure 	<ul style="list-style-type: none"> 33 keypad buttons with tactile feedback 5 Magnetic hall effect switches
Language options		English, Spanish, German, Italian, French

¹⁾ Totalizer switch inputs are not provided for the interface detector

Certificates and approvalsIP65 (NEMA 4X) flow display transmitter ratings

FM and CSA	I.S. Class I, II, Div 1 N-I Class I, Div 2 S Class II, Div 2
CE	EMC Directive 2004/108/EC LVD Directive 2006/95/EG C-TICK
ATEX	<ul style="list-style-type: none"> • Transmitter: Ex II (1) G [Ex ia] IIC EX II 3 (1) G Ex nC [ia] IIC T5 • Sensors: Ex II 1 G Ex ia IIC T5
INMETRO (Brazil)	<ul style="list-style-type: none"> • Transmitter: [BR-Ex ia] IIC BR-Ex nC [ia] IIC T5 • Sensors: BR-Ex ia IIC T5

IP65 (NEMA 7) compact explosion-proof enclosure ratings

FM and CSA	XP Class I, Div 1 D-I Class II, Div 1 I.S. Class I, Div 1 N-I Class I, Div 2 S Class II, Div 2 CE <ul style="list-style-type: none"> • EMC Directive 2004/108/EC • LVD Directive 2006/95/EG C-TICK
ATEX	<ul style="list-style-type: none"> • Transmitter: Ex II 2 (1) G Ex d [ia] IIB + H2 T5 • Sensors: Ex II 1 G Ex ia IIC T5
INMETRO (Brazil)	<ul style="list-style-type: none"> • Transmitter: BR-Ex d [ia] IIC T5 • Sensors: BR-Ex ia IIC T5

IP66 (NEMA 7) wall mount explosionproof enclosure ratings

FM and CSA	XP Class I, Div 1 D-I Class II, Div 1 I.S. Class I, Div 1 N-I Class I, Div 2 S Class II, Div 2
CE	EMC Directive 2004/108/EC LVD Directive 2006/95/EG
ATEX	<ul style="list-style-type: none"> • Transmitter: Ex II (1) G [Ex ia] IIC Ex II 3 (1) G Ex nC [ia] IIC T5 Ex II 2 (1) G Ex d [ia IIC] IIB + H2 T5 • Sensors: Ex II 1 G Ex ia IIC T5
INMETRO (Brazil)	<ul style="list-style-type: none"> • Transmitter: [BR-Ex ia] IIC BR-Ex d [ia IIC] IIB T5 • Sensors: BR-Ex ia IIC T5

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUH1010 (Oil)

Standard MLFB for quick delivery on SITRANS FUH1010 (Hydrocarbon liquid meter)

Selection and Ordering data	Order No.	Order code
SITRANS FUH1010 Oil clamp-on	L) 7ME360 - - - - - 0 - - - - -	K12 + K12 + R12
Design		
IP65 (NEMA 4X)	0	
Number of ultrasonic paths/meter type	4	
Dual path (DV-Standard Volume/Mass)		
Flowmeter functions and I/O configurations	A	
includes graphic or digital display, IP66 (BNB6665 (NEMA 4X)) and IP66 (NEMA 7 wall mounted) units:		
Standard		
• Graphic display		
• 4x 4 ... 20 mA analog input		
• 2x 0 ... 10 V		
• 2x 4 ... 20 mA		
• 2x pulse outputs		
• 4 Mercury wetted relays		
• 2x RTD input		
Meter power options	A	
90 ... 240 V AC		
Communication options	0	
RS 232 (standard)		
RTD temperature sensor		0
(includes mounting hardware for pipes above 1.5"/38 mm OD)		1
No RTDs		2
1 x standard clamp-on RTD		3
2 x standard clamp-on RTD		4
1 x submersible clamp-on RTD		
2 x submersible clamp-on RTD		
RTD		
Notes:		
1. Temperature input is required for FUH1010 systems		
2. Only the Interface detector set up as a dual channel can use 2 RTD's		
Sensor for channel 1		
(includes pipe mounting kit and spacer bar for indicated max. outer diam. listed)		
no sensor		A
C2H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	N
D1H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	P
D4H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	R
D1H (high precision)	High Temperature to 104 °C / 219 °F	Z
		P 1 P
Sensor for channel 2		
(includes pipe mounting kit and spacer bar for indicated max. OD listed)		
See „Sensor selection charts“ for specifications.		
no sensor		A
C2H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	N
D1H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	P
D4H (high precision)	Mounting frame and straps provided up to 1200 mm (48")	R
D1H (high precision)	High Temperature to 104 °C / 219 °F	Z
		Q 1 P
Approvals		
FM/CSA/CE/C-TICK (default)		1
ATEX, CE, C-TICK		2

Standard MLFB product offering represents 4 to 6 weeks delivery time

¹⁾ Supplied spacer bar supports pipes up to 750 mm (30"). For pipes larger than 750 mm (30") also, spare part 7ME3960-0MS40 (1012BN-4)

L) Subject to export regulations AL: N, ECCN: 3A991X.

For sensor and RTD cables for quick delivery see tables at end of section.

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUH1010 (Oil)

Selection and Ordering data

SITRANS FUH1010 Oil clamp-on

- IP65 (NEMA 4X) L) **7ME3600-**
- IP65 (NEMA 7) compact L) **7ME3601-**
- IP66 (NEMA 7) wall mounted L) **7ME3603-**

0 -

Sensor for channel/path 1 (continued)

For the following B1H to D4H sensors, temperature range is -1 °C up to 104 °C (30 °F up to 220 °F), nominal 65 °C (150 °F):

Sensor	Z	P	1	K
B1H (high temperature range HP)	Z	P	1	K
B2H (high temperature range HP)	Z	P	1	L
B3H (high temperature range HP)	Z	P	1	T
C1H (high temperature range HP)	Z	P	1	M
C2H (high temperature range HP)	Z	P	1	N
D1H (high temperature range HP) ¹⁾	Z	P	1	P
D2H (high temperature range HP) ¹⁾	Z	P	1	Q
D3H (high temperature range HP) ¹⁾	Z	P	1	U
D4H (high temperature range HP) ¹⁾	Z	P	1	R

Sensor for channel/path 2

(includes pipe mounting kit and spacer bar for indicated max. outer diameter listed)

See „Sensor selection charts“ for specifications

no sensor A

For the following A1H to D4H sensors, temperature range is -40 °C to 65 °C (-41 °F to 150 °F), nominal 21 °C (70 °F):

Sensor	H
A2H (high precision) Trackmount and straps provided up to 75 mm (3")	H
A3H (high precision) Trackmount and straps provided up to 75 mm (3")	J
B1H (high precision) Trackmount and straps provided up to 125 mm (5")	K
B2H (high precision) Trackmount and straps provided up to 125 mm (5")	L
B3H (high precision) Trackmount and straps provided up to 125 mm (5")	T
C1H (high precision) Mounting frame and straps provided up to 1200 mm (48") ¹⁾	M
C2H (high precision) Mounting frame and straps provided up to 1200 mm (48") ¹⁾	N
D1H (high precision) Mounting frame and straps provided up to 1200 mm (48") ¹⁾	P
D2H (high precision) Mounting frame and straps provided up to 1200 mm (48") ¹⁾	Q
D3H (high precision) Mounting frame and straps provided up to 1200 mm (48") ¹⁾	U
D4H (high precision) Mounting frame and straps provided up to 1200 mm (48") ¹⁾	R

Selection and Ordering data

SITRANS FUH1010 Oil clamp-on

- IP65 (NEMA 4X) L) **7ME3600-**
- IP65 (NEMA 7) compact L) **7ME3601-**
- IP66 (NEMA 7) wall mounted L) **7ME3603-**

0 -

For the following B1H to D4H sensors, temperature range is -1 °C up to 104 °C (30 °F up to 220 °F), nominal 65 °C (150 °F):

Sensor	Z	Q	1	K
B1H (high temperature range HP)	Z	Q	1	K
B2H (high temperature range HP)	Z	Q	1	L
B3H (high temperature range HP)	Z	Q	1	T
C1H (high temperature range HP)	Z	Q	1	M
C2H (high temperature range HP)	Z	Q	1	N
D1H (high temperature range HP) ¹⁾	Z	Q	1	P
D2H (high temperature range HP) ¹⁾	Z	Q	1	Q
D3H (high temperature range HP) ¹⁾	Z	Q	1	U
D4H (high temperature range HP) ¹⁾	Z	Q	1	R

Approvals

FM/CSA/CE/C-TICK (default), also for non hazardous area	1
ATEX	2
INMETRO (Brazil)	3

¹⁾ Supplied spacer bar supports pipes up to 750 mm (30 inches).

For pipes larger than 750 mm (30 inches) purchase also, spare part 7ME3960-0MS40 (1012BN-4)

L) Subject to export regulations AL: N, ECCN: 3A991X.

Selection and Ordering data

Further designs

Please add „-Z“ to Order No. and specify Order code(s).

Further designs	Order code
Cable assembly for sensors (add for # of paths) See „Sensor cable selection chart“	K..
Cable assembly for RTDs (add for # of RTDs) See „RTD cable selection chart“	R..
Cable termination kit (for one cable pair)	
• Termination for standard, plenum and armored sensor cable	T01
• Termination for submersible cable	T11
• RTD cable termination kit for standard RTD	T21
• RTD cable termination kit for submersible RTD	T31
Languages (Meter and Documentation), English (default)	
• German	B10
• French	B12
• Spanish	B13
• Italian	B14
Tag name plate	
• Stainless steel tags with 3.2 mm (0.13 inch) characters (68 characters max.)	Y19

Selection and Ordering data	Order No.
Operating Instructions for FUH1010	
English NEMA 4x & NEMA 7 Wall Mount Standard Volume	A5E02951449A
German NEMA 4x & NEMA 7 Wall Mount Standard Volume	A5E02951529A
English NEMA 4x & NEMA 7 Wall Mount Precision Volume	CQO:1010PVNFM-3
English NEMA 4x & NEMA 7 Wall Mount Interface Detector	CQO:1010BNFM-3
English NEMA 7 Compact Standard Volume	CQO:1010DVXFM-3
English NEMA 7 Compact Precision Volume	CQO:1010PVXFM-3
English NEMA 7 Compact Interface Detector	CQO:1010BXFM-3
This device is shipped with a Quick Start Guide and a CD containing further SITRANS F literature.	
All literature is also available for free at: http://www.siemens.com/flowdocumentation	

MLFB example

Application example

A clamp-on meter is required for a 12" carbon steel hydrocarbon line flowing multiple products, with a wall thickness of 12.7 mm (0.5"). Meter electronics are to be located in a Class I Div 2 area only 60 ft from the pipeline. 12 V DC power is available at the site.

Dual path operation is desired for improved accuracy and redundant measurement. Pulse output will be primary flow data source.

MLFB Order No.: **7ME3600-3CB00-3QQ1-Z**
K03 + K03 + R03

Selection and Ordering data	Order No.	Ord. code
FUH1010 meter family	7ME3600-3CB00-3QQ1-Z	
IP65 (NEMA 4X) enclosure	0	
Dual path precision volume	3	
Custody Transfer option with digital pulse	C	
9 ... 36 V DC power option	B	
RS232 Standard	0	
RTD required for viscosity comp	3	
Sensor code for path 1	Q	
Sensor code for path 2	Q	
FM approval required	1	
30 m (100 ft) sensor cable for path 1		K03
30 m (100 ft) sensor cable for path 2		K03
30 m (100 ft) cable for RTD		R03

Sensor Selection Chart

High precision sensors for steel pipe with outer diameter/wall thickness ratio >10

Sensor Size code	Order Code	Pipe wall (mm)		Pipe wall (inches)	
		min.	max.	min.	max.
A1H	G	0.64	1.02	0.025	0.04
A2H	H	1.02	1.52	0.04	0.06
A3H	J	1.52	2.03	0.06	0.08
B1H	K	2.03	3.05	0.08	0.12
B2H	L	3.05	4.06	0.12	0.16
C1H	M	4.06	5.84	0.16	0.23
C2H	N	5.84	8.13	0.23	0.32
D1H	P	8.13	11.18	0.32	0.44
D2H	Q	11.18	15.75	0.44	0.62
D4H	R	15.75	31.75	0.62	1.25
B3H	T	2.7	3.3	0.106	0.128
D3H	U	7.4	9.0	0.293	0.354

Sensor Cable Selection Chart

Sensor cable codes for length and type options

Cable length m (ft)	Standard (PVC jacket)	Submersible (polyethylene jacket)	Plenum Rated (teflon jacket)	Armored
	-40...+80 °C (-40...+176 °F)	-40...+80 °C (-40...+176 °F)	-40...+200 °C (-40...+392 °F)	-40...+80 °C (-40...+176 °F)
Order code				
6 (20)	K01¹⁾	K11	K21	K31
15 (50)	K02	K12¹⁾	K22	K32¹⁾
30 (100)	K03¹⁾	K13¹⁾	K23	K33
46 (150)	K04¹⁾	K14	K24	K34
61 (200)	K05	K15	K25	K35
91 (300)	K06	K16	K26	K36

RTD Cable Selection Chart

RTD cable codes for length and type

Cable length m (ft)	Standard (teflon wrapped)	Submersible (extruded jacket)
	-40 ... +200 °C (-40 ... +392 °F)	-40 ... +200 °C (-40 ... +392 °F)
Order code		
6 (20)	R01¹⁾	R11
15 (50)	R02¹⁾	R12
30 (100)	R03¹⁾	R13
46 (150)	R04	R14
61 (200)	R05	R15
91 (300)	R06	R16

¹⁾ Standard MLFB for quick delivery

FINE CONTROLS (UK) LTD



Fine Controls have been supplying process controls & instrumentation equipment since 1994, & now serves an ever expanding customer base, both in the UK & globally.

We offer a full range of valve & instrumentation products & services, with our product range representing leading technologies & brands:

Flow: Flow Meters & Transmitters, Flow Switches, Flow Control Valves & Batch Control Systems

Temperature: Temperature Probes & Thermowells, Temperature transmitters, Temperature Regulators & Temperature Displays

Level: Level Transmitters & Switches

Pressure: Pressure Gauges & Transmitters, Precision & High Pressure Regulators & I-P Converters, Volume boosters.

Precision Pneumatics: Pressure Regulators, I-P Converters, Volume Boosters, Vacuum Regulators

Valves: Solenoid & Pneumatic Valves, Control Valves & Positioners, Actuated Ball, Globe or Diaphragm Valves & Isolation Valves

Services: Repair, Calibration, Panel Build, System Design & Commissioning

 A rotork® Brand
FAIRCHILD



bürkert



SIEMENS



alcon
SOLENOID VALVES

A rotork® Brand



MIDLAND-ACS
A rotork® Brand



Honeywell



 **Bourdon**
Baumer Group



SOLDO
CONTROLS

A rotork® Brand



Fine Controls (UK) LTD, Bassendale Road, Croft Business Park,
Bromborough, Wirral, CH62 3QL UK
Tel: 0151 343 9966
Email: sales@finecontrols.com